



Dribble Bar II

On target for increased yields



The Dribble Bar II has a re-designed disc with 11 settings giving improved performance and features the unique 'dial-a-setting' flow rate adjustment

www.bfs.uk.com

Email: sales@bfs.uk.com • Tel: 01268 710237

BFS Dribble Bar

Accurately applies liquid fertiliser through four equally spaced openings along the Bar. The application rates can be pre-set to one of eleven different flow rates by a simple fingertip adjustment of the flow control dial.

These flow rates can be easily altered in the field without metering discs or removing the Dribble Bar.

Accurate: Allows precision targeting of liquid fertiliser, eradicates application overlap, and reduces lodging.

Effective: Provides an efficient and flexible method of application. Ensures liquid fertiliser can be applied under a wide range of climatic and ground conditions.

Economic: Offers increased speed, more efficient utilisation of men and machines and saves on cost by reducing waste.

Safe: Removes risk of drift contamination, run-off to ditches and hedgerows and minimises crop scorch.



BFS Dribble Bar Application Chart

		Pressure PSI	Flow G/min	Application Rate US Gallons per Acre @ 20 inch Spacing													
				3	4	5	6	7	8	9	10	11	12	13	14	15	16
Speed mph	15	0.29	28.2	21.2	16.9	14.1	12.1	10.6	9.4	8.5	7.7	7.1	6.5	6.1	5.6	5.3	
	18	0.32	31.6	23.7	19.0	15.8	13.6	11.9	10.5	9.5	8.6	7.9	7.3	6.8	6.3	5.9	
Position **	22	0.34	33.7	25.3	20.2	16.9	14.5	12.7	11.2	10.1	9.2	8.4	7.8	7.2	6.7	6.3	
	25	0.37	36.9	27.7	22.1	18.4	15.8	13.8	12.3	11.1	10.1	9.2	8.5	7.9	7.4	6.9	
	29	0.39	38.7	29.0	23.2	19.4	16.6	14.5	12.9	11.6	10.6	9.7	8.9	8.3	7.7	7.3	
	36	0.43	42.4	31.8	25.4	21.2	18.2	15.9	14.1	12.7	11.6	10.6	9.8	9.1	8.5	7.9	
Speed mph	15	0.30	29.3	22.0	17.6	14.6	12.6	11.0	9.8	8.8	8.0	7.3	6.8	6.3	5.9	5.5	
	18	0.33	32.4	24.3	19.5	16.2	13.9	12.2	10.8	9.7	8.8	8.1	7.5	6.9	6.5	6.1	
Position ▽	22	0.35	35.0	26.3	21.0	17.5	15.0	13.1	11.7	10.5	9.6	8.8	8.1	7.5	7.0	6.6	
	25	0.38	37.7	28.2	22.6	18.8	16.1	14.1	12.6	11.3	10.3	9.4	8.7	8.1	7.5	7.1	
	29	0.40	39.8	29.8	23.9	19.9	17.0	14.9	13.3	11.9	10.8	9.9	9.2	8.5	8.0	7.5	
	36	0.45	44.5	33.3	26.7	22.2	19.1	16.7	14.8	13.3	12.1	11.1	10.3	9.5	8.9	8.3	
Speed mph	15	0.36	35.3	26.5	21.2	17.7	15.1	13.2	11.8	10.6	9.6	8.8	8.1	7.6	7.1	6.6	
	18	0.41	40.3	30.2	24.2	20.1	17.3	15.1	13.4	12.1	11.0	10.1	9.3	8.6	8.1	7.6	
Position 1	22	0.44	43.7	32.8	26.2	21.8	18.7	16.4	14.6	13.1	11.9	10.9	10.1	9.4	8.7	8.2	
	25	0.48	47.1	35.3	28.2	23.5	20.2	17.7	15.7	14.1	12.8	11.8	10.9	10.1	9.4	8.8	
	29	0.50	49.7	37.3	29.8	24.8	21.3	18.6	16.6	14.9	13.6	12.4	11.5	10.6	9.9	9.3	
	36	0.54	53.4	40.0	32.0	26.7	22.9	20.0	17.8	16.0	14.6	13.3	12.3	11.4	10.7	10.0	
Speed mph	15	0.46	46.0	34.5	27.6	23.0	19.7	17.3	15.3	13.8	12.6	11.5	10.6	9.9	9.2	8.6	
	18	0.52	51.0	38.2	30.6	25.5	21.9	19.1	17.0	15.3	13.9	12.7	11.8	10.9	10.2	9.6	
Position 2	22	0.56	55.4	41.6	33.3	27.7	23.8	20.8	18.5	16.6	15.1	13.9	12.8	11.9	11.1	10.4	
	25	0.59	58.3	43.7	35.0	29.2	25.0	21.9	19.4	17.5	15.9	14.6	13.5	12.5	11.7	10.9	
	29	0.62	61.2	45.9	36.7	30.6	26.2	22.9	20.4	18.4	16.7	15.3	14.1	13.1	12.2	11.5	
	36	0.67	66.4	49.8	39.9	33.2	28.5	24.9	22.1	19.9	18.1	16.6	15.3	14.2	13.3	12.5	
Speed mph	15	0.58	57.5	43.2	34.5	28.8	24.7	21.6	19.2	17.3	15.7	14.4	13.3	12.3	11.5	10.8	
	18	0.65	64.1	48.1	38.4	32.0	27.5	24.0	21.4	19.2	17.5	16.0	14.8	13.7	12.8	12.0	
Position 3	22	0.71	70.1	52.6	42.1	35.0	30.0	26.3	23.4	21.0	19.1	17.5	16.2	15.0	14.0	13.1	
	25	0.74	73.8	55.3	44.3	36.9	31.6	27.7	24.6	22.1	20.1	18.4	17.0	15.8	14.8	13.8	
	29	0.78	77.4	58.1	46.4	38.7	33.2	29.0	25.8	23.2	21.1	19.4	17.9	16.6	15.5	14.5	
	36	0.86	84.7	63.6	50.8	42.4	36.3	31.8	28.2	25.4	23.1	21.2	19.6	18.2	16.9	15.9	
Speed mph	15	0.68	67.2	50.4	40.3	33.6	28.8	25.2	22.4	20.2	18.3	16.8	15.5	14.4	13.4	12.6	
	18	0.74	73.0	54.7	43.8	36.5	31.3	27.4	24.3	21.9	19.8	18.2	16.8	15.6	14.6	13.7	
Position 4	22	0.80	79.0	59.2	47.4	39.5	33.8	29.6	26.3	23.7	21.5	19.7	18.2	16.9	15.8	14.8	
	25	0.85	84.0	63.0	50.4	42.0	36.0	31.5	28.0	25.2	22.9	21.0	19.4	18.0	16.8	15.7	
	29	0.88	87.4	65.5	52.4	43.7	37.4	32.8	29.1	26.2	23.8	21.8	20.2	18.7	17.5	16.4	
	36	0.97	95.7	71.8	57.4	47.9	41.0	35.9	31.9	28.7	26.1	23.9	22.1	20.5	19.1	17.9	
Speed mph	15	0.77	76.4	57.3	45.8	38.2	32.7	28.6	25.5	22.9	20.8	19.1	17.6	16.4	15.3	14.3	
	18	0.85	84.2	63.2	50.5	42.1	36.1	31.6	28.1	25.3	23.0	21.1	19.4	18.0	16.8	15.8	
Position 5	22	0.91	90.5	67.9	54.3	45.2	38.8	33.9	30.2	27.1	24.7	22.6	20.9	19.4	18.1	17.0	
	25	0.97	96.0	72.0	57.6	48.0	41.1	36.0	32.0	28.8	26.2	24.0	22.1	20.6	19.2	18.0	
	29	1.00	99.1	74.3	59.5	49.6	42.5	37.2	33.0	29.7	27.0	24.8	22.9	21.2	19.8	18.6	
	36	1.10	109.3	82.0	65.6	54.7	46.9	41.0	36.4	32.8	29.8	27.3	25.2	23.4	21.9	20.5	
Speed mph	15	1.00	99.1	74.3	59.5	49.6	42.5	37.2	33.0	29.7	27.0	24.8	22.9	21.2	19.8	18.6	
	18	1.13	111.9	84.0	67.2	56.0	48.0	42.0	37.3	33.6	30.5	28.0	25.8	24.0	22.4	21.0	
Position 6	22	1.22	120.8	90.6	72.5	60.4	51.8	45.3	40.3	36.2	33.0	30.2	27.9	25.9	24.2	22.7	
	25	1.32	130.2	97.7	78.1	65.1	55.8	48.8	43.4	39.1	35.5	32.6	30.1	27.9	26.0	24.4	
	29	1.13	111.9	84.0	67.2	56.0	48.0	42.0	37.3	33.6	30.5	28.0	25.8	24.0	22.4	21.0	
	36	1.50	148.0	111.0	88.8	74.0	63.4	55.5	49.3	44.4	40.4	37.0	34.2	31.7	29.6	27.8	
Speed mph	15	1.15	114.0	85.5	68.4	57.0	48.9	42.8	38.0	34.2	31.1	28.5	26.3	24.4	22.8	21.4	
	18	1.27	126.1	94.5	75.6	63.0	54.0	47.3	42.0	37.8	34.4	31.5	29.1	27.0	25.2	23.6	
Position 7	22	1.38	136.8	102.6	82.1	68.4	58.6	51.3	45.6	41.0	37.3	34.2	31.6	29.3	27.4	25.6	
	25	1.48	146.5	109.8	87.9	73.2	62.8	54.9	48.8	43.9	39.9	36.6	33.8	31.4	29.3	27.5	
	29	1.62	160.1	120.0	96.0	80.0	68.6	60.0	53.4	48.0	43.7	40.0	36.9	34.3	32.0	30.0	
	36	1.76	173.9	130.4	104.4	87.0	74.5	65.2	58.0	52.2	47.4	43.5	40.1	37.3	34.8	32.6	
Speed mph	15	1.21	119.8	89.8	71.9	59.9	51.3	44.9	39.9	35.9	32.7	29.9	27.6	25.7	24.0	22.5	
	18	1.34	132.9	99.6	79.7	66.4	56.9	49.8	44.3	39.9	36.2	33.2	30.7	28.5	26.6	24.9	
Position 8	22	1.44	142.8	107.1	85.7	71.4	61.2	53.5	47.6	42.8	38.9	35.7	33.0	30.6	28.6	26.8	
	25	1.56	154.8	116.1	92.9	77.4	66.4	58.1	51.6	46.4	42.2	38.7	35.7	33.2	31.0	29.0	
	29	1.72	170.5	127.9	102.3	85.3	73.1	63.9	56.8	51.2	46.5	42.6	39.4	36.5	34.1	32.0	
	36	1.90	188.3	141.2	113.0	94.2	80.7	70.6	62.8	56.5	51.4	47.1	43.5	40.4	37.7	35.3	
Speed mph	15	1.25	124.0	93.0	74.4	62.0	53.1	46.5	41.3	37.2	33.8	31.0	28.6	26.6	24.8	23.2	
	18	1.40	138.6	104.0	83.2	69.3	59.4	52.0	46.2	41.6	37.8	34.7	32.0	29.7	27.7	26.0	
Position 9	22	1.51	149.6	112.2	89.8	74.8	64.1	56.1	49.9	44.9	40.8	37.4	34.5	32.1	29.9	28.0	
	25	1.64	162.1	121.6	97.3	81.1	69.5	60.8	54.0	48.6	44.2	40.5	37.4	34.7	32.4	30.4	
	29	1.78	175.7	131.8	105.4	87.9	75.3	65.9	58.6	52.7	47.9	43.9	40.6	37.7	35.1	33.0	
	36	1.98	195.6	146.7	117.4	97.8	83.8	73.4	65.2	58.7	53.4	48.9	45.1	41.9	39.1	36.7	



Fitting TeeJet/EF3/Euro Others + Cap
Part No. NFB200401 NFB200400
 (Please specify cap fitting when ordering)

